Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

RELIABILITY PREDICTION

Model : S-25 Data:2000-01-03

Style	**Part Type**	Q'ty	λ_g	π_Q	λ_{eg}	%
9.1	Resistor-Film, Insulated (RL)	20	0.003700	10	0.740000	24.486
9.1	Resistor-Film Power (RD)	2	0.010000	10	0.200000	6.618
9.1	Resistor-Wirewound Power (RW)	1	0.008500	10	0.085000	2.813
9.1	Resistor-Film, Variable (RVC)	1	0.040000	10	0.400000	13.235
9.1	Resistor-Thermistor (RTH)	1	0.001400	10	0.014000	0.463
10.1	Capacitor-Metal, Plastic (CH)	8	0.000510	10	0.040800	1.350
10.1	Capacitor-Ceramic(Gen.) (CK)	6	0.001700	10	0.102000	3.375
10.1	Capacitor-Aluminum Dry (CE)	6	0.001300	10	0.078000	2.581
6.1	Diode-Switching	3	0.000940	8	0.022560	0.746
6.1	Diode-Fast Recovery Power Rectifier	2	0.023000	8	0.368000	12.177
6.1	Diode-Power Rectifier / Schottky Power	4	0.002800	8	0.089600	2.965
6.1	Diode-Voltage Ref/Reg. (Avalanche & Zener)	2	0.003300	8	0.052800	1.747
6.1	Diode-Transient Suppressor/Varistor	1	0.002900	8	0.023200	0.768
6.4	Transistor-MOSFET	1	0.014000	8	0.112000	3.706
6.11	OPTO-isolator	2	0.027000	8	0.432000	14.294
6.11	OPTO-Emitter	1	0.000470	8	0.003760	0.124
5.1	Linear Microcircuits	2	0.009500	10	0.190000	6.287
11.1	Transformer Switching	1	0.000610	3	0.001830	0.061
11.2	Coil Fixed inductor or choke	2	0.000032	3	0.000192	0.006
17.1	Single Connections-Reflow solder	177	0.000069	1	0.012213	0.404
17.1	Fuses Clip-Clip Termination	2	0.000120	1	0.000240	0.008
22.1	Fuses	1	0.010000	1	0.010000	0.331
16.1	Plated Through Hole Circuit Boards	1	0.022000	2	0.044000	1.456
Total Failure rate:					3.022195	100%

- **Data Base: MIL-HDBK-217F ,Notice 2, Parts Count**
- **Env.: GB**

MTBF: 330885.33 **hrs**

Approved by: _____ . Compiled by: _____ .

A40-F009 89.01.03